



Unleash your full gaming potential with the Fast IPS G2470HS Red Eagle

Gain the competitive edge you need to unlock your full gaming potential with the 24" G2470HS monitor. Featuring an ultra-fast 0.2ms MPRT and a 180Hz refresh rate, this monitor ensures smooth gameplay. Armed with Adaptive Sync you can make split second decisions and forget about ghosting effects or smearing issues. The ability to adjust brightness and the dark shades with the Black Tuner delivers greater viewing performance in shadowed areas and the IPS panel technology guarantees superb image quality.



Fast IPS

The Fast IPS panel technology guarantees not only high-fidelity, vivid battleground scenes displayed with outstanding colour accuracy but provides also an outstanding 0.2ms Moving Picture Response Time (MPRT).



180Hz & 0.2ms MPRT

With 180Hz refresh rate and 0.2ms MPRT response time the force is with you! Make split second decisions and be sure the image on the screen is always sharp and smooth.

01 CHARAKTERISTIKA OBRAZU

| | |
|---------------------|---|
| Úhlopříčka monitoru | 23.8", 60.5cm |
| Panel | Fast IPS |
| Nativní rozlišení | 1920 x 1080 @180Hz (2.1 megapixel Full HD, DisplayPort) |
| Formát obrazu | 16:9 |
| Jas | 300 cd/m ² |
| Kontrast | 1000:1 |
| Pokročilý kontrast | 80M:1 |
| Čas reakce (MPRT) | 0.2ms |
| Úhel sledování | horizontální/vertikální: 178°/178°, na parvo/na lefo: 89°/89°, nahoru/dolů: 89°/89° |
| Barevná podpora | 16.7mln 8bit |
| Horizontalfrequenz | 30 - 225kHz |
| Arbeitsfläche H x B | 527 x 296.5mm, 20.7 x 11.7" |
| Velikost bodů | 0.275mm |
| Barva | matná, černá |

02 ROZHRANÍ / KONEKTORY / OVLÁDÁNÍ

| | |
|------------------------|---|
| Vstupní porty | HDMI x1 (v.1.4, max. 1920 x 1080 @180Hz) DisplayPort x1 (v.1.2, max. 1920 x 1080 @180Hz) |
| HDCP | ano |
| Konektor pro sluchátka | ano |

03 VLASTNOSTI

| | |
|------------------------|--|
| Redukce modrého světla | ano |
| Flicker Free LED | ano |
| Adaptive Sync support | HDMI: 1920 x 1080 @48-180Hz, DP: 1920 x 1080 @48-180Hz |
| Extra | i-Style Colour |
| Jazyky OSD | EN, DE, FR, ES, IT, PT, RU, JP, CZ, NL, PL |
| Kontrolní tlačítka | Signal select/ Exit, + / Volume, - / i-Style Colour, Menu, Power |
| Nastavitelné parametry | picture adjust (contrast, brightness, overdrive, ACR, ECO, Black Tuner, MBR, gamma), input select (input source), audio adjust (volume, mute), store user settings (user modes), colour settings (colour temperature, 6-Axis, user preset), image adjust (i-Style colour, X-Res Technology, sharp & soft, HDMI range, direct drive mode, video mode adjust), language, setup menu (OSD H. position, OSD V. position, OSD time, opening logo, Adaptive Sync, LED, DDC/CI, USB BC), display information, reset |
| Reproduktory | 2 x 2W |
| Výhoda | Kensington-lock™ připraven, DDC2B, Mac OSX |

04 MECHANICKÉ ČÁSTI

| | |
|----------------------|-------------------------|
| Úpravy polohy | náklon |
| Úhel náklonu | 21.5° nahoru; 3.5° dolů |
| VESA | 100 x 100mm |
| Systém správy kabelů | ano |

05 ZAHRNUTÉ PŘÍSLUŠENSTVÍ

| | |
|--------|--------------------|
| Kabely | napájecí, HDMI, DP |
|--------|--------------------|

Ostatní

uživatelský manuál, instrukce bezpečnosti

06 POWER-MANAGEMENT**Napájecí zdroj:** interní**Napájení** AC 100 - 240V, 50/60Hz**Odběr energie:** 18W typisch, 0.5W odpočinek, 0.3W vypnutý**07 UDRŽITELNOST****Předpisy** CE, TÜV-Bauart, EAC, PSE, RoHS support, ErP, WEEE, VCCI, REACH, UKCA, Eyesafe 2.0**Energetická třída (Regulation (EU) 2017/1369)** E**REACH SVHC** nad 0.1% olova**08 ROZMĚRY / HMOTNOST****Rozměry výrobku Š x V x D** 539.5 x 393.5 x 192.5mm**Rozměry balení Š x V x D** 610 x 413 x 126mm**Váha (bez balení)** 3.2kg**EAN code** 4948570124466

Všechny ochranné známky jsou registrovány a chráněny. Vyhrazené právo na změny. Veškeré ploché panely LCD splňují normu ISO-9241-307:2008 v oblasti počtu vadných pixelů.

© IIYAMA CORPORATION. ALL RIGHTS RESERVED